

FOCIS Flex – No Wireless Fiber Optic Connector Inspection System

NEW



Features

- Removes Bluetooth and WiFi features for secure network facility compliance
- Auto-focus and auto-centering for fast, easy inspection
- Untethered operation simplifies access at patch panels
- IEC, IPC and user-defined pass/fail analysis
- Self-contained, compact, hand-held inspection solution
- Save results internally
- Ergonomic design fits in the palm of your hand
- Generate inspection reports using aeRos or TRM® 2.0

Applications

- Inspect connectors on patch cords or in bulkhead adapters
- Optical network installation, troubleshooting and maintenance
- Inspect MPO/MTP multi-fiber connectors
- Assure critical fiber infrastructure performs properly
- Keep fiber connections working at optimal performance levels
- Verify proper connector cleaning practices are being used

The FOCIS Flex NW addresses the need of network maintenance contractors operating in secure environments, where devices emitting radio frequency (RF) communication signals are prohibited, such as government and defense facilities and restricted private enterprise network facilities. The FOCIS Flex NW removes, in both hardware and software, Bluetooth and WiFi communications transceiver functions. It includes internal storage for 10,000 ferrule end-face images and pass/fail results, as well as a USB mass storage device interface, so that inspection results can be transferred at the end of the workday.

Pass/fail results in seconds: With the press of a single button, FOCIS Flex NW auto-focuses, captures and centers the end-face image, applies pass/fail rules, and displays image and pass/fail results. All in a matter of seconds!

Independent, untethered operation: With rechargeable battery supply and integrated display, FOCIS Flex NW can be used independently – without requiring an external OTDR or display unit.

Save results internally or externally: FOCIS Flex NW internally stores thousands of results using file-naming capabilities similar to FlexScan and FlexTester OTDRs. A micro-USB port supports fast upload of internally stored results to PC, and ensures your FOCIS Flex NW software can be updated to the latest features and supported languages.

Wide range of adapter tips: Interchangeable adapter tips support connector inspection for a wide range of both single-fiber and multi-fiber patchcords and bulkhead-mounted connectors having either PC or APC polished end-faces.

FOCIS Flex NW is available in standalone kit configurations including soft carry case/holster and user-selected adapter tips.

FOCIS Flex – No Wireless Fiber Optic Connector Inspection System

Specifications ^a

OPTICAL PERFORMANCE	
Field of View (viewed on FOCIS Flex)	Live: 710 x 860 µm; Captured, Zoomed Out: 560 x 600 µm; Captured, Partially Zoomed In: 360 x 390 µm; Captured, Fully Zoomed In: 180 x 195 µm
Field of View (Viewed on a PC)	Stored, Zoomed Out: 700 x 525 µm; Stored, Fully Zoomed In: 240 x 180 µm
Manual Detection Capability	1 µm
Analysis Resolution	1.5 µm
Captured Image Size (Pixels)	648 x 480 VGA; Images stored internally in three .JPG files, one at each FOV
OPERATING FEATURES	
Focus	Auto-focus and manual focus
Centering	Auto-centering after capture
Pass/Fail Analysis	IEC 61300-3-35 (2015), IPC and user-defined criteria
Image Capture and File Storage Capacity	10,000 files
File Format (Image and Pass/Fail Results)	jpg, gif
USB Characteristics	USB 1.1 mass storage device
Supported Languages	English, French, German, Japanese, Spanish, Polish, Russian
PHYSICAL AND POWER CHARACTERISTICS	
Display size, type, resolution	2.4", TFT, 240 x 320 with brightness control
Battery Type	NiMH, user replaceable
Battery Operating Time (typical)	8 hours (60 tests in 20 minutes each hour; auto-off enabled)
Recharge Time	<4.5 hours
Power Save Features	Auto-off (disabled, 2, 5, 10 minutes)
AC Charger voltage, frequency, current	100-240 V, 50/60 Hz, 5VDC, 2A
Size	47 x 37 x 183 mm (1.8 x 1.5 x 7.2 in)
Weight	240 g (0.5 lb)
ENVIRONMENTAL CHARACTERISTICS	
Operating Temperature	0 to +50 °C
Storage Temperature	-40 to +70 °C
Relative Humidity	95%, non-condensing
Transit and shock	2G vibration, 30G shock

Notes:

a. All specifications valid at 23°C ±2°C (73.4°F ±3.6°F).

FOCIS Flex – No Wireless Fiber Optic Connector Inspection System

Ordering Information

DESCRIPTION	AFL NO.
FOCIS Flex Kit, soft carry case / holster, USB cable, AC charger, TRM 2.0 reporting software, reference guide, no tips, no BT or WiFi wireless functionality	FOCIS-FLX-NW-P4XN
FOCIS Flex Kit, soft carry case / holster, USB cable, AC charger, TRM 2.0 reporting software, reference guide, 2 user-selected UPC adapter tips (ferrule and bulkhead), user-selected One-Click cleaner, no BT or WiFi wireless functionality	FOCIS-FLX-NW-P4XU
FOCIS Flex Kit, soft carry case / holster, USB cable, AC charger, TRM 2.0 reporting software, reference guide, 2 user-selected APC adapter tips (ferrule and bulkhead), user-selected One-Click cleaner, no BT or WiFi wireless functionality	FOCIS-FLX-NW-P4XA

FOCIS Flex Adapter Tips (Contact AFL for adapter tips for other connector types)

DESCRIPTION	AFL NO.
SC-UPC bulkhead adapter tip	FFLX-01-SC
FC-UPC bulkhead adapter tip	FFLX-01-FC
ST-UPC bulkhead adapter tip	FFLX-01-ST
LC-UPC bulkhead adapter tip	FFLX-01-LC
Universal 2.5 mm, UPC ferrule adapter tip	FFLX-01-U25
Universal 1.25 mm, UPC ferrule adapter tip	FFLX-01-U125
SC-APC bulkhead adapter tip	FFLX-01-ASC
FC-APC bulkhead adapter tip	FFLX-01-AFC
LC-APC bulkhead adapter tip	FFLX-01-ALC
Universal 2.5 mm, APC ferrule adapter tip	FFLX-01-A25
Universal 1.25 mm, APC ferrule adapter tip	FFLX-01-A125
FOCIS Flex adapter extension tube, straight, 46 mm	FFLX-01-EXTS46
FOCIS Flex adapter extension tube, straight, 80 mm:	FFLX-01-EXTS80
E2000 PC/UPC bulkhead adapter tip	DFS1-00-0023MR
E2000 APC bulkhead adapter tip	DFS1-01-0008MR
Tip for SC/APC (OptiTap®) bulkhead adapter	DFS1-01-0007MR
Tip for OptiTip® APC ferrule and bulkhead adapter	DFS1-01-0013MR
Multi-row MTP/PC ferrule & bulkhead adapter extended tip kit (base plus multi-row MTP/PC front end tip)	DFS1-00-0050MR
MTP/PC ferrule & bulkhead adapter extended tip kit (base plus MTP/PC front end tip)	DFS1-00-0037MR
MTP/PC and MTP/APC ferrule & bulkhead adapter extended tip kit (base, MTP/PC, MTP/APC front end tips)	DFS1-00-0042MR
MTP/APC ferrule and bulkhead adapter extended tip kit (base plus MTP/APC front end tip)	DFS1-01-0010MR



International Sales and Service Contact Information

Available at www.AFLglobal.com/Test/Contacts