Mini Termination Box - LTU Series (Indoor)

Features

- SLIDE-IN-LOCK fiber optic splice tray with> 90° opening angle
- Suitable for cable jointing or distribution
- Quick installation and easy maintenance design
- ROHS compliance
- Rugged and durable construction for long term reliability (UV resistance)
- Engineering plastic material
- Compact and lightweight
- No special tools needed
- Reusable
- Fixing device for reinforced core included
- Wall mount and desktop applications
- Comply with TIA / EIA 568B, Bellcore GR-326, IEC6 0 8 7 4-10, Telcordia, JIS compliance

Specifications

Parameter	
Splice Capacity (Max.) - Single	24
No. of Splice Trays (Max.)	1
No. of Adaptor (Max.)	8
No. of Cable Entry Ports (Max.)	3
Optic Cable Dimensions (Max.)	2 (16mm) or 3 (16mm x1 & 1mm x2)
Main Material	Plastic (PC)
Colour	White
Product Dimensions (Height) (Width) (Depth)	264 mm 154 mm 56 mm

Product Gallery

Ordering Information

PN	Number of Port	Types of Adapter	Mode Type
LTO	02 - 2 port 04 - 4 port ---------- 16 - 16 port	FC - FC adapter SC - SC adapter ST - ST adapter LC -LC adapter	S - Singlemode/UPC A - Singlemode/APC M - Mutlimode 3 - OM3 Aqua 4 - OM4

L	T	O	0	2	F	C	S

* Ordering Code Example

Website: www.lightem.com | Email: info@lightem.com
Tel: +852-26875815 | Fax: +852-26875456