Mini Termination Box - LTX

Features

- Window cuts as small as 50mm possible with specific cable constructions such as the TE Mini-breakout cable
- Drop cables can be directed to 4 different sides by rotating the splice module on the base module
- Rugged and durable construction for long term reliability (UV resistance)
- Free breathing enclosure for indoor use
- Front accessible
- Wrap around riser cable installation
- Not required to cut loop-through fibers from riser cable
- Can hold 4 LC connectors or 2 SC connectors
- Compatible with mechanical splice, heat shrink protectors in the same splice holder

Specifications

Parameter	Value
Splice Capacity (Max.) - Single	4
No. of Splice Trays (Max.)	4 (4 different sides)
No. of Adaptors (Max.)	8 LC or 4 SC
No. of Cable Entry Ports (Max.)	4 main ports
Optic Cable Dimensions (Max.)	Main cable (10.5); Drop cable (5mm)
Main Material	Cold Rolled Steel
Colour	Black
Product Dimensions (Height) (Width) (Depth)	200mm 110mm 35mm

Product Gallery

Ordering Information

PN	No. of Ports	Type of Adaptor	Mode Type
LTX	02 - 2 Ports 04 - 4 Ports ---------- 08 - 8 Ports	FC - FC adaptor SC - SC adaptor ST - ST adaptor LC - LC adapter	S - Singlemode UPC A - Singlemode APC M - Multimode 3 - OM3 Aqua 4 - OM4

L	T	X	0	2	F	C	M

* Ordering Code Example

Website: www.lightem.com | Email: info@lightem.com
Tel: +852-26875815 | Fax: +852-26875456